


ELIPSE® HALF-FACE MASK +HESPA[™] ABEK1P3 DUST (R) Filters









Standards EN140: 1998 Mask Body EN14387: 2004 + A1: 2008 ABEK1P3 R D CE 2797

Efficiency

P3 >99,95% for 0,3 µ particulate At 1000 ppm: Cyclohexane (C₆H₁₂) > 70 minutes Chlorine (Cl₂) > 20 minutes Hydrogen súlphide (H_3S) > 40 minutes Hydrogen cyanide (HCN) > 25 minutes Sulphur dioxide (SO₂) > 20 minutes Ammonia (NH₃) > 50 minutes

Weight

Mask + Filter: net (S/M) 367 g; (M/L) 384 g gross (S/M) 478 g; (M/L) 485 g Filter: net 142,5 g each; both net 285 g, gross 308 g

Shelf Live

3 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Material

- Mask: Medical grade TPE Conforms to ISO 10993-10: 2010 for irritations. Mask body latex and silicone free, odour free.
- Valve Body in Nylon, Inhalation/Exhalation diaphragm in Silicone. 4 point adjustable elasticated head and neck strap with comfort pad in TPE.
- Gas Filters: Activated carbon sealed into a ABS Shell.
- Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element.

Production

United Kingdom, Italy, Romania 100% of filters NaCl Tested



Applications - Universal gases, dust, mist and fumes

Type Δ R Ε K

P

Protection

organic gases and vapours with a boiling point above 65°C inorganic gases and vapours (excluding carbon monoxide) sulphur dioxide and other acidic gases and vapours

ammonia and organic ammonia derivatives

dust



ISSUE date 18/02/21 ISSUE n. 3