

Benchmark**BMG342**

WATER REPELLENT FULLY-COATED DUAL LATEX GRIP GLOVE

A flexible glove fully coated with smooth latex and sandy latex palm offering powerful grip properties. Ideal for heavy duty handling tasks and when exposed to changeable weather conditions.

FEATURES

- › Full smooth latex coating coupled with an additional latex sandy coating to the palm and fingertips
- › Seamless 13 gauge nylon knitted liner
- › Water repellent
- › Long lasting grip performance in wet and dry conditions
- › Good abrasion and tearing properties
- › Soft, comfortable fit
- › Anatomical hand shape design helps prevent hand fatigue
- › Oeko tex® certified



SUITABLE FOR

Typical Industries

- Agriculture
- Construction
- Landscaping
- Logistics
- Rail
- Renewables
- Utilities

Suitable Applications

- Handling Construction Materials
- Transportation
- Labouring
- Outdoor Wet Work
- Warehousing
- Maintenance

CERTIFICATION

CAT II

EN 388:2016



3131X

See overleaf for explanation

Benchmark**BMG342****PRODUCT INFORMATION**

MATERIALS	LINER:	13 gauge nylon
	COATING:	Full smooth latex with sandy latex on palm
COLOUR	Blue/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	BMG00342DD	10 pairs per bag
8/M	BMG00342DF	120 pairs per case
9/L	BMG00342DH	
10/XL	BMG00342DJ	
11/XXL	BMG00342DL	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for heat, thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- **WARNING:** Latex may cause allergies

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)
				Impact Resistance	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globus.co.uk

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | BMK-DATA-BMG342-0621_1