

ULTIM8

THE ULTIMATE RESISTANCE

The most advanced protection for extreme work environments (cold/hot/dust/humid environments/oil&gas industries, mining...).

ULTIM8 offers a maximal resistance to fogging thanks to PLATINUM® coating.



ULTIPSI



RUSHKITS
Retainer strap
(for spectacle version)



Worn as goggle



64 g

SUPPLIED WITH

Transformation kit:
removable temples



Worn as spectacle with
temples kit



Worn as spectacle with
temples kit and retainer
strap (option)



Pivoting temples

+ PIVOTING PC/TPR TEMPLES

+ SEALED TPR FOAM

+ REMOVABLE AND ADJUSTABLE STRAP

+ SPECTACLE/GOGGLE TRANSFORMATION KIT

+ PLATINUM® (P) COATING

bolle
SAFETY

ULTIM8

THE ULTIMATE RESISTANCE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
ULTIM8	Clear	ULTIPSI	2C-1.2 1 BT KN €€	☐ EN166 FT €€ temples version ☐ EN166 3 4 5 BT €€ goggle version	Anti-scratch/Anti-fog (P)
Retainer strap	Strap	RUSHKITS	-	☐ EN166 3 4 5 BT €€	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

€€ European standard ☐ Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets.

4. Large dust particles > 5 microns.

5. Gas and fine dust particles < 5 microns.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard ☐ Manufacturer name

Bolle Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY



This permanent coating on both sides of the lens gives them a high resistance to scratching, to the most aggressive chemicals and delays the onset of fogging. In all circumstances and at all times the PLATINUM® lens innovation guarantees your eyes improved protection.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bolle Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE

	ULTIPSI
Individual plastic bag	366074008079
10 safety spectacles per box	3660740108076
240 safety spectacles per outer pack	3660740208073

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
STRAP	15mm adjustable - Polyester
FOAM	TPR



30/08/2017

Europe Bolle Safety
95 rue Louis Guérin
89100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bolle Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com

bolle
SAFETY