

A825 / A825P

A827 / A827P

NITRILE COATED SAFETY GLOVES USER INFORMATION


GLOVE DESCRIPTION

The gloves have a heavy weight Nitrile coating. The inner liner is a 100% jersey, with a cotton wristing or canvas safety cuff. The gloves are excellent for all round general handling situations.

GLOVE SERIES

A825 Knitted Wrist Fully Coated
A825P Knitted Wrist Palm Coated
A827 Safety Cuff Fully Coated
A827P Safety Cuff Palm Coated

MARKING

 , STYLE, SIZE AND C €

GLOVE SIZES AVAILABLE	
Hand Size defined in EN 420	Glove Sizes
8	SMALL
9	MEDIUM
10	LARGE
11	X-LARGE

INTERMEDIATE
Safety Category



4221



Mechanical test data in accordance with EN388:2003

Abrasion	Resistance	Level 4
Cut	Resistance	Level 2
Tear	Resistance	Level 2
Puncture	Resistance	Level 1

The result are taken from the palm area of the gloves

Caution : DO NOT USE near moving machinery if

there is any risk of entanglement.

SGS UNITED KINGDOM LTD., 202B WORLEY PARKWAY,
WESTON-SUPER-MARE, BS22 6WA, UNITED KINGDOM,
(Notified Body No. 0120)

CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before use, especially after cleaning treatment, and before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exists, before removal from the hands. Excess contaminant should first be removed and the gloves may be decontaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands.

PACKING AND STORAGE

The gloves are packed in bundles, along with this leaflet. The bundled gloves are then placed in cardboard cartons. This is suitable for transportation and storage. Store the gloves in cool dry place and out of direct sunlight.

OBsolescence

Stored correctly, the gloves physical properties will not change for up to five years.

GENERAL

The quality system used to manufacture the gloves is in compliance with ISO 9001. None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer.

PLEASE NOTE

Hand protection is limited to the Nitrile Rubber coated areas of the Glove. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. The results of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the gloves suitability for the intended use.

Further information is available at the below address.

Ultimate Industrial Ltd.

Victoria House, Colliery Road, Horseley Fields,
Wolverhampton, WV1 2RD, UK