

B1601 - T-REX MID/T-WALL

Collection: Fortrex

Upper: Water-Resistant Nubuck

Insole: TPR Cap

Lining: SmellStop Antibacterial

Toecap: SlimCap

Sole: Rubber

Outer Carton: 10

Fortrex

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345: 2011 S3

Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Anti-static footwear
- Shock absorption in the heel region
- Hydrocarbons resistant
- Water resistant upper
- Heat resistant 1 minute up to 300°C
- Heat insulation up to 150°C
- Cold insulation up to -17°C
- Men's width

B1601 - T-REX MID/T-WALL **Commodity Code: 6403993300**

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-05707-22 Rev. 1

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-05707-22 Rev. 1

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | DUN14 |
|------------|--------|------|------|------|------------|------------------------|---------------|-------|
| B1601BRO36 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530122419 | |
| B1601BRO37 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530122426 | |
| B1601BRO38 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530122433 | |
| B1601BRO39 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530122440 | |
| B1601BRO40 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530122457 | |
| B1601BRO41 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122464 | |
| B1601BRO42 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122471 | |
| B1601BRO43 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122488 | |
| B1601BRO44 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122495 | |
| B1601BRO45 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122501 | |
| B1601BRO46 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122518 | |
| B1601BRO47 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122525 | |
| B1601BRO48 | | 68.0 | 55.0 | 38.0 | 0.9990 | 0.1421 | 8052530122532 | |