

Uci C€ Minimal Risks BA13

Acrylic/Spandex gloves

INTENDED TO PROTECT THE WEARER AGAINST:

- Mechanical action whose effects are **minimal** and **easily reversible**.
- Handling hot components not exposing the wearer to temperatures above 50 C.
- Atmospheric agents of neither exceptional nor extreme nature.
- Minor impacts and vibrations which do not effect vital areas of the body and where the effects cannot cause irreversible lesions.

INSTRUCTIONS FOR USE:

CLEANING / MAINTENANCE Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Aprons should not be left in a contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. Cleaning of this product is NOT recommended.

STORAGE Gloves should be ideally stored in dry conditions in the original package and out of direct UV light.

OBSOLESCENCE When stored as recommended will not suffer change in mechanical properties for up to 3 years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of the user to ascertain the suitability of the glove for the intended use.

GENERAL None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer.

PLEASE NOTE The results of physical tests should help in product selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine product suitability for the intended use.