

ELIPSE INTEGRA® HALF-FACE MASK + HESPA[™] A2P3 DUST (R) Filters



FILTER TECHNOLOGY





Standards

EN140: 1998 Mask Body EN14387: 2004 + A1: 2008 A2P3 R D EN166 Class 1.B.K.N. (Anti-Fog & Anti-Scratch) CE 2797

Efficiency P3 >99,95% for 0,3 µ particulate At 5000 ppm: Cyclohexane (C_6H_{12}) > 35 minutes

Weight

Mask + Filter: net (S/M) 399 g; (M/L) 404 g gross (S/M) 538 g; (M/L) 544 g Filter: net 121 g each; both net 242 g, gross 265 g

Shelf Live

3 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Material

- Mask: Medical grade TPE Conforms to ISO 10993-10: 2010 for irritations. Mask body latex and silicone free, odour free.
- Valve Body in Nylon, Inhalation/Exhalation diaphragm in Silicone.
- 4 point adjustable elasticated head and neck strap with comfort pad in TPE.
- Gas Filters: Activated carbon sealed into a ABS Shell.
 Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element.
- Goggle: Polycarbonate with flow coating overmolded into soft TPE, permanently attached to the mask body by stainless steel clips.

Production

United Kingdom, Italy, Romania 100% of filters NaCl Tested

	Code	Description	Quantity
R	SPR536 (S/M) SPR537 (M/L)	A2P3 Reusable Half Mask for multiple Gases and Vapours and Dust	10 pcs. per box
a	SPR497	A2P3 replacement filters	5 sets of 2 pcs. per box
Ja	SPM520	Peel off visor x 10	10 sets per box
N	SPR523	Cases for P3 filters	15 sets of 2 pcs. per box
	SPM524	Pair of P3 filters	15 sets of 2 pcs. per box

Applications - Universal gases, dust, mist and fumes

Manufacturing



Agriculture Pesticides



Car & Ship Repair Epoxite, Paint, Solvants

ISSUE date 18/02/21 ISSUE n. 3