

COBRA™ GRINDING VISOR

PRODUCT CODE: AFC061-320-400

CLEAR FACESHIELD IDEAL FOR USE WHEN DRESSING WELDS

TECHNICAL SPECIFICATION

EYE & FACE PROTECTION

INSTRUCTIONS FOR USE

Before use, the browguard should be fitted to the Visor.

In use ensure that the Faceshield fits comfortably and securely on the head

Ensure that the visor is in place before entering the hazard area

PERFORMANCE

Offers protection against medium energy high speed particles at 120 m/s (270 mph), liquid droplets and molten metal

The optical qualities of the visor comply with the requirements of optical class 1 (highest).

LIMITATIONS OF USE

Protection will only be offered if the faceshield is fitted correctly

If the visor becomes scratched or damaged it should be replaced

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals

If this occurs leave the hazard area, remove the faceshield and seek medical advice

Polycarbonate visors are not suitable for use with all chemicals – if you are unsure contact your supplier or JSP for help and advice

CLEANING & MAINTENANCE

The browguard and visors may be cleaned with soap and warm water and dried with a soft cloth. The unit should not be cleaned with chemical or abrasive cleaners

Store out of direct sunlight, away from chemicals and not exposed to extremes of temperature



BROWGUARD
Polypropylene

VISOR
Polycarbonate

Wheel Ratchet Harness
Polythene C/W ABS,
Nylon & Steel Fittings

DIMENSIONS

Height -> 18cm

Width -> 26cm

Length -> 29cm

Weight -> 0.32kg

CONFORMITY

Conforms to EN 166.1.B.9