

LITEGUARD SPECIALIST FACESHIELD

A STRONG YET LIGHTWEIGHT BROWGUARD WITH AN ELASTICATED ADJUSTABLE HEAD HARNESS & RANGE OF SCREENS

**TECHNICAL
SPECIFICATION**

EYE & FACE PROTECTION

INSTRUCTIONS FOR USE

Before use, the browguard should be fitted to the visor

In use, ensure that the Faceshield fits comfortably and securely on the head

Ensure that the visor is in place before entering the hazard area

MATERIALS

Browguard: Polypropylene

Head Harness: Nylon

Visor: 1mm Polycarbonate

DIMENSIONS OF OUTER PACKAGING

Quantity: 15

Height: 5900mm

Width: 4300mm

Length: 4500mm

Weight: 11Kg (Approx)

FACESHIELD FEATURES & PERFORMANCE

Offers protection against medium energy high speed particles at 120m/s (270mph), liquid droplets and molten metal

The optical qualities of the visor comply with the requirements of optical class 1 (highest)

A strong yet lightweight browguard, the LiteGuard features an elasticated adjustable head harness and range of screens

Available with a metal bound clear polycarbonate screen (200mm)

CLEANING & MAINTENANCE

The browguard may be cleaned with soap and warm water and dried with a soft cloth

Do not clean with chemical or abrasive cleaners

The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature



CONFORMITY

The LiteGuard conforms to EN 166 1.B.3

DIMENSIONS OF FACESHIELD

Height: 330mm

Width: 250mm

Length: 200mm

Weight: 0.75Kg (Approx)

LIMITATIONS OF USE

Protection will only be offered if the faceshield is fitted correctly
If the faceshield becomes scratched or damaged they should be replaced

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the faceshield and seek medical advice