







CAT II

USER INFORMATION

KUTLASS ORANGE PU300-12-OR

GLOVE SERIES: KUTLASS ORANGE PU 300-12-OR

MARKING:  Style,  SIZE, , & 

GLOVE SIZE AVAILABLE

HAND SIZE DEFINE IN EN 420:2003	GLOVE SIZE
6	XS/6
7	S/7
8	M/8
9	L/9
10	XL/10
11	XXL/11

AVAILABLE VARIANTS

Palm Coated version, Knuckle Coated Version, Full Coated Version, gauntlet Version, Velcro Closure version

FEATURE

These gloves are machine knitted from cut resistant fibres, blended with and Other synthetic yarn and coated with Ployurethane to provide a good resistant barrier. These gloves offer excellent dexterity and offer good wet, dry or oily grip. These gloves offer good mechanical protection against tears and abrasion in dry handling conditions.

NOTE: These gloves resist cuts but are NOT cut proof. Do not use near high speed or serrated blades.

AVOID USING NEAR MOVING MACHINERY DUE TO ENTANGLEMENT HAZARDS.

CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Don't use chlorine bleaches.

Note: The performance characteristics of worn and laundered gloves may differ from the results shown below.

STORAGE

Gloves should be ideally stored in dry and cool conditions in original package, away from direct sunlight.

OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and it is the responsibility of user to ascertain suitability of the glove for its intended use.

GENERAL

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

PLEASE NOTE

The results of the physical tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use.



EN 388:2003



4 3 4 3

This Pictogram indicates that the product protects against Mechanical risks and complies under EN 388. The numbers indicate performance levels.

(INTERMEDIATE)

Safety Category

4 Abrasion Resistance

3 Cut Resistance

4 Tear Resistance

3 Puncture Resistance

Test results are taken from the palm area of the gloves.

All EC type examinations were carried out by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom. (Notified Body No. 0321) in accordance with EU directive 89/686/EEC

Further information may be obtained from the address below.

Ultimate Industrial Ltd,

Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK

316030