## **SUPERTOUCH®**





EC Council Directive 89/686/EEC

Plastic Materials and Articles in Contact with Food Regulation (EU) No 10/2011 EN ISO 374-1:2016 - 40% Sodium Hydroxide

EN ISO 374-5:2016 - Protection against bacteria and fungi (not tested against viruses)

## PRODUCT INFORMATION

## **PG-901 Diamond Grip Nitrile**

## **Description:**

These robust and durable gloves feature a unique "diamond grip" texture across their surface, allowing for outstanding grip - even when being used in greasy environments. The PG901 is made from a heavy-duty nitrile featuring tough tear resistance without compromising dexterity. Along with excellent stretch the glove is also extremely easy to don and remove thanks to its polymer coating.

- ✓ Conforms to EN ISO 374-1:2016 Type C
- ✓ AQL 4.0
- CAT III
- Polymer Coated
- Chemical resistant
- Level 5 dexterity
- Food Approved
- ✓ 100% Latex Free
- ✓ Ambidextrous
- ✓ Textured grip
- ✓ Powder Free
- ✓ Single use only
- √ 100 pieces per dispenser sizes S-L
- ✓ 90 pieces per dispenser size XL

#### Material:

- Nitrile

### **Applications:**

Tasks include automotive, engineering, agriculture, general use, cleaning & janitorial, care home work & chemical handling.

## **Product Codes:**

12781-4 S-XL PG-901 Diamond Grip - Orange

## Colourways:



Orange

## Standards:











from powder




Product does not contain latex



Do not reuse



with food



## Size Chart:

Measurements in mm	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)
Hand Length (A)	171	182	192	204	215
Hand Circumference (B)	178	203	229	254	279

Issue No.: 2 Issue Date: 09/04/2018

# **SUPERTOUCH®**

Packaging: 100 pieces per dispenser in sizes Small - Large. 90 pieces per dispenser in size XLarge - 10 dispensers per case

#### **Outer Carton Artwork:**



### **Inner Artwork:**



The information shown on this specification sheet is intended as a guide and is advisory only. All details were correct at the time of issue. As conditions of use are ultimately beyond our control, we advise that the product is tested for the particular application before use.