PORTWEST. USER INFORMATION

RFF: 5USP



FN ISO 20471 RIS-3279 EN 343 CERTIFIED





В	INCHES	CM	EURO
XS	32"-34"	80-88	40-44
S	36"-38"	92-96	46-48
M	40"-41"	100-104	50-52
L	42"-44"	108-112	54-56
XL	46"-48"	116-124	58-62
XXL	50"-52"	128-132	64-66
3XL	54"-55"	136-140	68-70
4XL	56"-58"	144-148	72-74
5XI	60"-64"	152-160	76-80

c	INCHES	СМ	DE	FR
XS	26-28	68-72	42-44	34-36
S	30-32	76-80	46-48	38-40
M	33-34	84-88	50	42-44
L	36-38	92-96	52-54	46-48
XL	40-41	100-104	56	50-52
XXL	42-44	108-112	58-60	54-56
3XL	46-47	116-120	62	58-60
4XI	48-50	124-128	64-68	62-64

MANUFACTURER

PROFHUESI, ΠΡΟИЗВОДИТЕЛ, PROIZVOĐAČ, VÝROBCE, TOOTJA, VALMISTAJA, FABRICANT, HERSTELLER, KATAZKEYAZTHZ, GYÁRTÓ, FABBRICANTE, RAŽOTĀJS, GAMINTOJAS, ПРОИЗВОДИТЕЛ, PRODUSENT, PRODUCENT, FABRICANTE, PRODUCATOR, ПРОИЗВОДИТЕЛЬ, PROIZVOĐAČ, VÝROBCA, PROIZVAJALEC, TILLVERKARE, ÜRETICI, BUPOБНИЯ

PORTWEST, WESTPORT, CO MAYO, IRELAND

TEST HOUSE

AGJENSIA E TESTIMIT, ЛАБОРАТОРИЯ ЗА ИЗПИТВАНЕ, ISPITNA KUĆA, ZKUŠEBNÍ DŮM, TESTHUIS, TEST MAJA, TESTAAJA, ORGANISME NOTIFIE, TESTIERHAUS, ΔΟΜΗ ΔΟΚΙΜΩΝ, TEST HOUSE, LABORATORIO, TESTA VIETA, TESTAVIMO ISTAIGA, TECT KYKA, TESTORGAN, LABORATORIUM BADAJĄCE, CASA DE TESTE, ИСПЫТАТЕЛЬНЫЙ ЦЕНТР, ISPITNA KUĆA, CERTIFIKAČNÝ ORGAN, TESTNA HIŠA, LABORATORIO DE ENSAYOS, TESTHUS, TEST KURULUŞU, ВИПРОБУВАЛЬНИЙ ЦЕНТР

INTERTEK The Warehouse, Brewery Lane, Leigh, WN7 2RJ UK

Notified body number: 0362

Wyndham Way, Telford Way, Kettering, Northamptonshire, SATRA

NN16 8SD. United Kingdom Notified body number: 0321

Bracetown Business Park, Clonee, Dublin 15, D15 YN2P Ireland Notified Body: 2777

Vartest Laboratories, Inc., 19 West 36th Street,

10th Floor New York, NY 10018, ISO/IEC 17025 Testing Certificate No.

through A2LA is 2180.01

Plaza Emilio Sala 1, 03801 Alcov, Alicante, Spain

Notified body number: 0161

OTI Institut fur Okologie, Technik und Innovation GmbH, Spengergasse

20 1050 Vienna, Austria Notified body number: 0534

PORTWEST USER INFORMATION

Please read these instructions carefully before using this safety clothing. You should also consult your safety officer or immediate superior with regard to suitable garments for your specific work situation. Store these instructions carefully so that you can consult them at any time.



Refer to the product label for detailed information on the corresponding standards Only standards and icons that appear on both the product and the user information below are applicable. All these products comply with the requirements of Regulation (FII 2016/425)

(B) (C) ◐

ISO 13688:2013 Protective Clothing (See label)

General Requirements This Furnnean A Standard specifies general requirements for ergonomics, ageing, sizing, marking of protective clothing and for information supplied by the manufacturer.

- A= Recommended height range of wearer
- R= Recommended chest girth of wearer
- C= Recommended waist girth of wearer
- D= Recommended inside leg measurement of wearer



EN ISO 20471:2013 + A1:2016, High Visibility Warning Clothing signalling the users presence during day and night (see label)

X Classifications (EN ISO 20471:2013 + A1:2016) X Class for the fluorescent and reflective surface - 3 levels

Class 1 - Minimum level traffic speeds <30km/h Class 2 -Intermediate level traffic speeds < 60km/h Class 3 -Highest level traffic speeds >60km/h



RIS-3279-TOM Issue 1 (2016) -

Railway Industry Standard

RIS-3279-TOM Issue 1 has replaced GO/RT 3279 Railway Industry Standards (RIS) are mandatory on all members of the Railway Group and apply to all relevant activities

Limitations of use:

(EN ISO 20471:2013 + A1:2016, RIS 3279 & ANSI/ISEA 107-2015): Always wear the garment fastened. Keep clean: Should the High Visibility properties of this garment become irrecoverably soiled or contaminated, replace with a new one. This garment is suitable for wear during an entire working day and contains no toxic substances that can affect health adversely in any other way. No allergic reactions due to skin contact with this garment are known. Do not attempt to repair damaged garments. All garments should be discarded safely. The clothing should not be altered or fitted with extra labels or logos. The clothing should only be worn in situations for which it is intended...

Limitations of use (RIS 3279): Class 1 trousers claiming RIS 3279 Compliance are required to be worn with a RIS 3279 upper body garment.

Tumble dry normal



thermal lining

EN 343: 2019 Protection Against Rain (see label)

X Resistance to water penetration 4 levels

Y Resistance to water vapour penetration 4 levels

R Readymade garmet rain tower test,optional 'R' symbol may be replaced by an 'X' symbol if test not carried

out or not suitable. X Class 1 Minimum level Y Class 1 Minimum level Class 2 Class 2 Class 3 Clare 2

Class 4 Highest level Class 4 Highest level Garments with removable sleeves only offer full protection when the sleeves are attached to the body of the garment. Recommended maximum continuous wearing time for a complete suit consisting of jacket and trousers without a

Temp 25°C	Class 1 60	Class 2	Class 3	Class 4
	60			
		105	180	
20°C	75	250		_
		_		
	240	_		-
5°C	_	_		
	15°C 10°C 5°C	15°C 100 10°C 240 5°C	15°C 100 10°C 240 5°C	15°C 100

" Means no limit for wearing time Water Vapour Resistance effect for coated fabrics or laminates in different ambient temperatures

Available Size & Selection

Fit according to correct chest and waist size, refer to size chart. These garments have built in allowance for comfort and to allow the garment to be worn over medium bulky dothing.

Storage:

DO NOT store in places subject to direct or strong sunlight. Store in clean, dry conditions. Please ensure hood is fully dry before packing/storing away.

After-care: The manufacturer will not accent liability for

garments where care labels have been ignored, defaced or removed

Fibre Content Label:

Refer to garment label for corresponding content details. Where there is a hood, peripheral vision and hearing may

he impaired

Retroreflective tape and labels:

Retroreflective tape or labels should not be ironed! Please refer to the garment label for the number and wash cycles claimed. The stated maximum number of cleaning cycles is not the only factor related to the lifetime of the garment. The lifetime will also depend on usage, care storage, etc. Garments should be discarded when the protective qualities no longer apply eq. 1. Maximum number of washes is reached, 2. The material has been damaged either by fading or has been torn. 3. The reflective qualities of the tape have faded. 4. Garment is permanently soiled, cracked, burned or heavily abraded.

Wash C	are Labels: Refer to garment label for corres	ponding	washing details.		
30°	Max temp 30°C, mild process		Line dry	MAX	Maximum
40°	Max temp 40°C, mild process	Ш	Drip line dry	50 x	50 Washes
40°	Max temp 40°C, normal process	\bowtie	Do not iron	MAX 25x	Maximum 25 Washes
60°	Max temp 60°C, normal process	\equiv	Iron max 110°C	MAX	Maximum
$ \otimes $	Do Not Bleach	\equiv	Iron max 150°C	12 x	12 Washes
Ø	Do not tumble dry	Ø	Do not dry clean	MAX	Maximum
\odot	Tumble dry low	(P)	Professional dry clean	5 x	5 Washes

VARTEST

AITEX