



WATCH THE VIDEO
Vimeo.com/Pyramex/H2MAX



Cappture™ ANSI • CE • CSA •



DIELECTRIC

Dielectric // Fits over prescription glasses //
Temples extend from browbar to avoid interference
with prescription frame's temples // Rubber gasket
option is available

Lens and Temples | 2 Variations

ES9910ST ••• Clear **H2X** AF
ES9920ST ••• Grey **H2X** AF

Rubber Gasket | 1 Variation

ES9910STMGRG ••• Clear **H2MAX** AF

Part No.	Lens Marking	Temple Marking
ES9910ST	2C-1.2 P 1FT CE	CE P EN166 FT
ES9920ST	5-2.5 P 1FT CE	CE P EN166 FT
ES9910STMGRG	2C-1.2 P 1FT KN CE	CE P EN166 FT

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
5 or 6: Solar filter

Colour Perception

C: Unimpaired colour perception

Protection Class

1.2 - 6: Degree of visible light
filtration

Optical Class

1: High optical quality - no optical
distortion

Mechanical Strength

F: Low energy impact, resists a 6
mm, .86 g at 45 m/s
T: Impact protection at extreme
temperature conditions

Symbols

P: Manufacturer's mark
K: Resistance to surface damage
by fine particles
N: Filter with anti-fog
CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
P: Manufacturer's mark
EN166: CE specification for
protective eyewear

Mechanical Strength

F: Low energy impact
T: Impact protection at extreme
temperature conditions

General Specifications

Weight: 29.5 gm | 51.7 gm with rubber gasket

Bridge: 23.1 mm

Lens base: 2.5 curve

Lens size diagonal: 145.7 mm

Lens size vertical: 51.5 mm

Lens thickness: 1.8 mm

Overall length (lens - tip): 160 mm

Overall width (hinge - hinge): 132.5mm

Closest point between temple tips: 88 mm

Materials

Lens: polycarbonate

Nosepiece: polycarbonate

Temple: polycarbonate

Hinge: nylon + polycarbonate

Rubber gasket: polycarbonate and thermoplastic
rubber (TPR)

