

# RUSH+ SMALL

## FOR HEALTHCARE PROFESSIONALS

This advanced eye protection **adapted to narrow faces** was specifically designed for healthcare professionals; its design combines ultimate protection and comfort to help reduce workplace accidents. Equipped with **Platinum® anti-scratch and anti-fog coating** on both sides of the lens, RUSH+ SMALL ensures long-lasting comfort, performance and reliability.

†PLATINUM®



Non-slip  
adjustable bridge

**RUSH+ is customized for:**  
lens marking, colored temples...

**Information & conditions :** [marketing@bolle-safety.com](mailto:marketing@bolle-safety.com)

26 g

- + **UPPER PROTECTION**
- + **†PLATINUM® ANTI-FOG & ANTI-SCRATCH COATING (†P)**
- + **CO-INJECTED, ULTRA-FLEX TEMPLES**
- + **NON-SLIP ADJUSTABLE BRIDGE**
- + **WASHABLE AND REUSABLE**

**bolle**  
SAFETY

# RUSH+ SMALL

## FOR HEALTHCARE PROFESSIONALS

MODEL	VERSIONS	REFERENCES	LENS MARKINGS			FRAME MARKINGS			COATINGS
			EN166	ANSI	AS/NZS	EN166	ANSI	AS/NZS	
<b>RUSH+ SMALL</b>	Clear	PSSRUSP0862	ZC-1.2  1 FT KN	Z87+ U6	IO	EN166 FT	Z87+	AS/NZS 1337.1	Anti-scratch/Anti-fog

### LENS MARKING

Manufacturer name

#### Optical class symbols:

**1.** Continuous work

#### Mechanical strength symbols:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

**K.** Resistance to surface damage by fine particles

**N.** Resistance to fogging

European standard

**Z87+ =** Impact rated for Plano product  
Tested and approved to ANSI Z81.1-2015

#### Lens type

- Clear = none
- Welding = W and scale number from 1.3 to 14
- UV filter = U and scale number from 2 to 6
- Visible light filter = L and scale number from 1.3 to 10
- IR filter = R and scale number from 1.3 to 10
- Variable tint = V
- Special purpose = S

**O.** Range of luminous transmittance 80-100% (clear)

### TECHNOLOGIES

#### PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



Europe Bollé Safety  
34 Rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
e-mail: contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead  
Road - Chessington Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

APAC  
Bollé Safety AU Pty Limited  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: sales@bollesafety.com.au

**bolle-safety.com**

### FRAME MARKING

Manufacturer name

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorizes use for high speed particles at extreme temperatures.

European standard

**Z87+ =** Impact rated for Plano product  
Tested and approved to ANSI Z81.1-2015

**Country of origin:** Taiwan

**ANSI:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

**AS/NZS 1337.1:2010 :** Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

**Bollé Safety product approval certificates to standards will be sent on request.**

### CHARACTERISTICS

<b>LENSES</b>	<b>PC - 2,2 mm - Curve 9</b>
<b>FRAME</b>	-
<b>TEMPLES</b>	<b>PC + TPR</b>
<b>SPARE LENSES</b>	<b>No</b>

### PACKAGING AND EAN13 CODE

	<b>PSSRUSP082</b>
<b>Individual plastic bag</b>	3660740013059
<b>10 safety glasses per inner box</b>	3660740113056
<b>200 safety glasses per outer pack</b>	3660740213053

27/07/2021

**bolle**  
SAFETY