# M9800 PANOVIEW

## **BLACK ARMS - CLEAR HC LENS**

ADJUSTABLE TEMPLE LENGTH AND SOFT FLEXIBLE NOSE PADS PROVIDE COMFORT, REDUCED SLIPPAGE AND OUTSTANDING FIELD OF VISION

## MARTCARE® RANGE

SPECIFICATION

TECHNICAL

## **INSTRUCTIONS FOR USE**

In use ensure that the safety spectacles fit comfortably and securely on the head  $% \left( {{{\bf{n}}_{\rm{s}}}} \right)$ 

Ensure that the safety spectacles are in place, before entering the hazard area

#### PERFORMANCE

Lens offers protection against low energy high speed particles at 45m/s (101mph)

The optical qualities of the lens comply with the requirements of optical class 1 (highest)

### **DIMENSIONS OF INNER & OUTER PACKAGING**

Inner –
Height: 101mm Width: 155mm Length: 254mm Weight: 460g
Quantity: 10
Outer -
Height: 425mm Width: 275mm Length:800mm Weight: 10kg
Quantity: 200

## **CONFORMITY & MARKINGS**

Conforms to EN166:2001
Markings –
Frame: EN166: 2001 - F
Clear Lens: 🌡 1.F

## **CLEANING & MAINTENANCE**

The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth

Do not clean with chemical or abrasive cleaners

The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperataure



MATERIALS
Frame: Polycarbonate
Side Arms: Polycarbonate
Lens: Polycarbonate

## **LIMITATIONS OF USE**

Protection will only be offered if the safety spectacles are fitted correctly with lenses being inserted correctly
If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately
Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals
If this occurs leave the hazard area, remove the eye shield and seek medical advice
The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer
These safety spectacles are not suitable for protection against dusts, liquids or molten metals

 $(\square)$ 

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jsp.co.uk.



MANUFACTURING FOR SAFETY

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050 0000

leenod 91/06