

# ACEGRIP

## Supported Natural Rubber Work Glove.

### GLOVE DESCRIPTION

The gloves have a medium weight rough Natural Rubber coating. The liner is a Polyester cotton machine knitted shell. The gloves give all round performance and they are suitable for most construction work and general industrial assembly operations.

The gloves are actifresh / sanitized treated to provide protection against micro-organism which may give rise to bad odours and the risk of cross infections.

### GLOVE SERIES


W1-251-NL-C

### MARKING

UCI, ACEGRIP, SIZE AND 

GLOVE SIZE AVAILABLE	
Hand size defined in EN 420	Glove Sizes
7	7
8	8
9	9
10	10

INTERMEDIATE  
Safety category



3 1 4 2

Mechanical test data in accordance with EN 388

Abrasion	Resistance	Level 3
Cut	Resistance	Level 1
Tear	Resistance	Level 4
Puncture	Resistance	Level 2

The results are taken from the palm area of the gloves. All EC type examinations were carried out by S.G.S United Kingdom Ltd., Ellesmere Port, CH65 3 EN, United Kingdom.  
(Notified Body No 0120)

## **CLEANING / MAINTENANCE**

Both new and used gloves should be thoroughly inspected before use, especially after cleaning treatment, and before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exists, before removal from the hands. Excess contaminant should first be removed and the gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed with out the contaminant contacting the bare hands.

## **PACKING AND STORAGE**

The gloves are packed in bundles, along with this leaflet. The bundled gloves are then placed in cardboard cartons. This is suitable for transportation and storage. Store the gloves in cool dry place and out of direct sunlight.

## **OBSOLESCENCE**

Stored correctly, the gloves physical properties will not change for up to five years.

## **GENERAL**

The quality system used to manufacture the gloves is in compliance with ISO 9001:2008. None of the materials or process used in the manufacture of these products is known to be harmful to the wearer.

## **PLEASE NOTE**

The information contained herein is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitability for the intended use.

Warning: Gloves not be worn when there is a risk of entanglement by moving part of machines.

Latex warning: Some individual may experience allergic sensitive rubber latex.

Further information is available at the below address.

**Victoria House  
Colliery Rd  
Wolverhampton  
WV1 2RD**