



CE0194

CE0086

EN149:2001
+A1: 2009

MANUFACTURER

Portwest Limited, Westport, Co Mayo, Ireland

NAME & ADDRESS OF THE NOTIFIED BODY HAVING ISSUE EC CERTIFICATE:

INSPEC INTERNATIONAL LTD - NOTIFIED BODY: 0194

56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom
MODELS: P102-P153-P203-P223-P271-P273- P304-P351-P371

BSI GROUP - NOTIFIED BODY 0086

Kitemark Court - Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP - UK
MODELS: P100-P101-P108-P200-P201-P209-P220-P250-P251-P291-P301-
P303-P309-P391



CERTIFIED PRODUCT :

AUSTRALIAN & NZ STANDARD BMP: 672774

MODELS: P100-P101-P200-P201-P220-P250-P251



EN

USER INFORMATION

DUST MASK - PARTICLE FILTER HALF MASK

Refer to the product label/markings for detailed information on the corresponding standards. Only standards and icons that appear on both the product and the user information below are applicable. All these products comply with the requirements of Regulation (EU 2016/425) and compliant with standard EN149:2001+A1:2009.

This mask is classified in accordance with its filtering capacity and maximum total inward leakage.

The mask must be chosen according to the type of contaminant, its concentration (see material data safety sheet) and the protection factors (APF) allocated by national laws. For more information, consult standard EN529 (Recommendations for selection, use, servicing and maintenance).

There are three equipment classes: FFP1 / FFP2 / FFP3 (see marking on box and on mask).

FFP1: Protective mask against solid and liquid particles without specific toxicity. Filter efficiency of the filtering medium: 80%. Total Inward Leak < 22%. Allocated Protection Factor (APF) : 4. Examples of applications: Handling of stone / rubble / cellulose.

FFP2: Protective mask against solid and liquid particles of average toxicity. Filter efficiency of the filtering medium: 94%. Total Inward Leak < 8%. Allocated Protection Factor (APF) : 10. Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics / cutting, deburring, grinding, drilling of metal.

FFP3: Protective mask against solid and liquid particles of high toxicity. Filter efficiency of the filtering medium: 99%. Total Inward Leak < 2%. Allocated Protection Factor (APF) : 20. Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement.

INSTRUCTIONS FOR USE:

1. Hold the preformed mask in the palm of your hand, with the nose bar towards the top and the straps hanging down.
2. Place the mask under your chin, covering your mouth and nose.
3. Take the upper elastic strap and pass it around the back of your head, take the lower elastic strap and pass it round the back of your neck.
4. Mould the nose bar around the nose to seal it off completely.
5. Check the seal by breathing out hard and ensure that no air leaks around the sides of the mask. If necessary, readjust and check again.

This mask should not be used for more than single shift. This mask must only be used once (no maintenance). Only take the mask out of its packaging just before you are going to use it. Only use when the concentration of contaminants does not pose an immediate risk to life or health, and only in accordance with local applicable health and safety standards. Before you

use the mask, check that it is undamaged, that its expiry date has not been reached (see the box) and that the protection class (FFP1 / FFP2 / FFP3) is appropriate for the product used and its concentration.

LIMITS TO USAGE:

Do not use other than for the scope of use defined in the above instructions for use. Contact with the skin may cause allergic reactions in people with sensitive skin. In this event, leave the area of risk, remove the mask and seek medical advice.

WARNING:

The user must have adequate training in the wearing of the mask and must have read the instructions before using it. Use the mask in well-ventilated areas, where there is no lack of oxygen (> 19.5%) and where there is no explosive atmosphere.

The mask must be positioned correctly in order to provide the expected level of protection. Do not use if facial hair (beard, sideburns) prevents the mask from being fully sealed, and leakage is detected.

Leave the area immediately if you experience breathing problems and/or dizziness or faintness.

Do not make any modifications to the mask, and discard it if there is any damage to it
This dust mask DOES NOT PROTECT the user against gases or vapours and solvents from spray painting.
Failure to observe these instructions for use may have adverse effects on the health of the user and expose him to serious or even life-threatening risks.

STORAGE INSTRUCTIONS:

Store in a cool, dry place away from frost and light in their original packaging (-10°C/+50°C - HR<80%).
The storage period, under these conditions, is limited to 5 years.



TEMPERATURE RANGE OF STORAGE CONDITIONS



MAXIMUM RELATIVE HUMIDITY OF STORAGE CONDITIONS