

B0895 - Be-Dry Mid/Be-Rock S3 WR CI HI HRO SRC

Collection: Special

Upper: Water-Resistant Full Grain Leather with H2st0p Membrane

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: AirTech Double-Density PU/HRO Rubber Life Plus Technology

Outer Carton: 10

Special

Special footwear for extreme work.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

UNI EN ISO 20345:2012 S3 (WR CI HI HRO SRC)

Features

- Anti-static footwear
- Water resistant upper
- Metal free
- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Water resistant shoe
- Heat resistant 1 minute up to 300°C
- Heat insulation up to 150°C
- Cold insulation up to -17°C
- Hydrocarbons resistant

B0895 - Be-Dry Mid/Be-Rock S3 WR CI HI HRO SRC **Commodity Code: 6403993300**

Test House

A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)

Via Alberto Riva Villasanta, 3

, Italy

Cert No: F-113-04031-21 (Be-Dry Mid) & F-113-04032-21 (Be-Rock)

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: 0161_24672_17

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
B0895BRR39	Brown	67.0	57.0	36.0	1.4230	0.1375	8054633492291	
B0895BRR40	Brown	67.0	57.0	36.0	1.4900	0.1375	8054633492307	
B0895BRR41	Brown	67.0	57.0	36.0	1.6000	0.1375	8054633492314	
B0895BRR42	Brown	67.0	57.0	36.0	1.6500	0.1375	8054633492321	
B0895BRR43	Brown	67.0	57.0	36.0	1.7500	0.1375	8054633492338	
B0895BRR44	Brown	67.0	57.0	36.0	1.7900	0.1375	8054633492345	
B0895BRR45	Brown	67.0	57.0	36.0	1.8100	0.1375	8054633492352	
B0895BRR46	Brown	67.0	57.0	36.0	1.9600	0.1375	8054633492369	
B0895BRR47	Brown	67.0	57.0	36.0	1.9700	0.1375	8054633492376	
B0895BRR48	Brown	67.0	57.0	36.0	1.9980	0.1375	8054633492383	
B0895BRR49	Brown	67.0	57.0	36.0	2.1380	0.1375	8054633492390	
B0895BRR50	Brown	67.0	57.0	36.0	2.1210	0.1375	8054633492406	