

## B0666B - YELLOWSTONE

**Collection:** Record

**Upper:** Microfibre + Hi-Tech Fabric

**Insole:** TPR Cap

**Lining:** SmellStop Antibacterial

**Midsole:** Fresh'n Flex

**Toecap:** SlimCap

**Sole:** AirTech + Tpu-Skin

**Outer Carton:** 10

### Record

Record antifatigue footwear collection offers an answer to the demand for lightweight design.

### Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



### Standards

EN ISO 20345: 2011 S3 (FO ESD SR)

CEI EN 61340-4-3 S3

### Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Anti-static footwear
- Electronic devices protection from electrostatic discharges
- Hydrocarbons resistant
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Metal free
- Men's width
- Women's width
- SRC - Slip resistant outsole to prevent slips and trips on ceramic and steel surfaces

**B0666B - YELLOWSTONE**  
**Commodity Code: 6404199000**

**Test House**

Cert No: N° F-113-05777-22

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	DUN14
B0666BBKR35		68.0	41.0	38.0	1.0300	0.1059	8052530126776	
B0666BBKR36		68.0	41.0	38.0	1.0350	0.1059	8052530125748	
B0666BBKR37		68.0	41.0	38.0	1.0440	0.1059	8052530125755	
B0666BBKR38		68.0	41.0	38.0	1.0660	0.1059	8052530125762	
B0666BBKR39		68.0	41.0	38.0	1.1310	0.1059	8052530125779	
B0666BBKR40		68.0	41.0	38.0	1.1510	0.1059	8052530125786	
B0666BBKR41		68.0	41.0	38.0	1.2060	0.1059	8052530125793	
B0666BBKR42		68.0	41.0	38.0	1.2290	0.1059	8052530125809	
B0666BBKR43		68.0	41.0	38.0	1.2950	0.1059	8052530125816	
B0666BBKR44		68.0	41.0	38.0	1.3050	0.1059	8052530125823	
B0666BBKR45		68.0	41.0	38.0	1.3550	0.1059	8052530125830	
B0666BBKR46		68.0	41.0	38.0	1.4260	0.1059	8052530125847	
B0666BBKR47		68.0	41.0	38.0	1.4580	0.1059	8052530125854	
B0666BBKR48		68.0	41.0	38.0	1.5020	0.1059	8052530125861	