


Manufactured from a robust polycarbonate frame, FRESNA™ safety glasses do not contain any metal parts and so help protect eyes from electric arcs that may form while working on electrical equipment or heavy machinery. The slimline temple design boosts comfort when worn with ear defenders.

SPECIAL FEATURES

- 100% metal-free
- Wide angle vision
- Close fitting lateral protection
- Universal nose bridge
- Slim temples enhance comfort when worn with ear defenders
- Supplied with neck cord
- Weight: 26g
- 8-Base lens



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	● RLY00071	2-1.2 CE 1FT CE	CE EN 166 FT CE	Impacts, UV radiations	Riley Anti-scratch and Anti-fog
AMBER	● RLY00073	2-1.2 CE 1FT CE	CE EN 166 FT CE	Impacts, UV radiations	
GREY	● RLY00072	5-2.5 CE 1FT CE	CE EN 166 FT CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification ➔

GENERAL SPECIFICATION

LENS BASE	8mm
WEIGHT	26g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Polycarbonate	One piece moulded universal
TEMPLE	Polycarbonate	Robust and durable
HINGE	Nylon	Metal-free and durable

LENS MARKINGS

LENS FILTER TYPE:

- 2 UV
- 5 Solar

SCALE NUMBER (SHADE):

- 1.2 Clear or Amber
- 2.5 Grey

Identity of manufacturer

OPTICAL CLASS:

- 1 High optical quality

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

- K Resistance to scratches by fine particles
- N Resistance to fogging

Certification mark

FRAME MARKINGS

Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM