

REF: 5SP




EN ISO 2071
RIS-3279
EN 343
CERTIFIED



	A	D
	CM	CM
SHORT	152-164	74
REG	164-176	79
TALL	176-188	84
X TALL	188-202	92

B	INCHES	CM	EURO
XS	32"-34"	80-88	40-44
S	36"-38"	92-96	46-48
M	40"-41"	100-104	50-52
L	42"-44"	108-112	54-56
XL	46"-48"	116-124	58-62
XXL	50"-52"	128-132	64-66
3XL	54"-55"	136-140	68-70
4XL	56"-58"	144-148	72-74
5XL	60"-64"	152-160	76-80

C	INCHES	CM	DE	FR
XS	26-28	68-72	42-44	34-36
S	30-32	76-80	46-48	38-40
M	33-34	84-88	50	42-44
L	36-38	92-96	52-54	46-48
XL	40-41	100-104	56	50-52
XXL	42-44	108-112	58-60	54-56
3XL	46-47	116-120	62	58-60
4XL	48-50	124-128	64-68	62-64



MANUFACTURER

ПРОДЮСЕР, ПРОИЗВОДИТЕЛ, ПРОДЮСИЧ, УПРОСЕР, ТОВАТА, МАШИНАТА, ФАБРИКАТ, НЕСТЕЛЕР, КАТАЛОЖЕНТИ, ГИЯТИ, ФАБРИКАНТЕ, РАЗОВИЯ, ГАМИТОВИЯ, ПРОИЗВОДИТЕЛ, ПРОДИСИЧ, ПРОДУКТ, ФАБРИКАНТЕ, ПРОДУКАТ, ПРОИЗВОДИТЕЛ, ПРОДЮСЕР, УПРОСЕР, ПРОИЗВАЈАТЕЛ, ТИЛВЕЈЕР, ЏРЕТИК, ВИРОСНИК.

PORTWEST, WESTPORT, CO MAYO, IRELAND

TEST HOUSE

АГЕНСИЈА Е ТЕСТИМАТ, ЛАБОРАТОРИЈА ЗА ИЗПИТУВАЊЕ, ИСПИТНА КУЌА, ЗКУШЕЊНИ ДОМ, ТЕСТИНУМ, ТЕСТ МАЈА, ТЕСТАЈА, ОРГАНИСМЕ НОТИФИ, ТЕСТИЕРИУСА, ДОМНИ ДОКЛИМ, ТЕСТ HOUSE, ЛАБОРАТОРИО, ТЕСТА ВЕИТА, ТЕСТАВИО СТАНГА, ТЕСТ КУЈА, ТЕСТОРГАН, ЛАБОРАТОРИУМ БАДАЈЕСЕ, САСА ДЕ ТЕСТЕ, ИСПИТАТЕЛНИ ЦЕНТР, ИСПИТНА КУЌА, СЕРТИФИКАЦИОН ОРГАН, ТЕСТНА ИЅА, ЛАБОРАТОРИО ДЕ ЕНСАВОС, ТЕСТУШ, ТЕСТ КУРУЛУШ, ВИПРОБУВАЛНИ ЦЕНТР

- INTERTEK** The Warehouse, Brewery Lane, Leigh, WN7 2RJ UK
Notified body number: 0362
- SATRA** Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom **Notified body number: 0321**
Bracetown Business Park, Clonee, Dublin 15, D15 YN2P Ireland
Notified Body: 2777
- VARTSEST** **Vartest Laboratories, Inc., 19 West 36th Street,**
10th Floor New York, NY 10018, ISO/IEC 17025 Testing Certificate No. through AZLA is 2180.01
- AITEK** Plaza Emilio Sala 1, 03801 Alcoy, Alicante, Spain
Notified body number: 0161
- OTI** Institut für Ökologie, Technik und Innovation GmbH, Spengergasse
20 1050 Vienna, Austria **Notified body number: 0534**



Please read these instructions carefully before using this safety clothing. You should also consult your safety officer or immediate superior with regard to suitable garments for your specific work situation. Store these instructions carefully so that you can consult them at any time.

Refer to the product label for detailed information on the corresponding standards. Only standards and icons that appear on both the product and the user information below are applicable. All these products comply with the requirements of Regulation (EU 2016/425).



EN 343 : 2003 + A1:2007
Protection Against Rain (see label)

- X Resistance to water penetration **3 levels**
- Y Resistance to water vapour penetration **3 levels**

- X Class 1 Minimum level
Class 2 Intermediate level
Class 3 Highest level
- Y Class 1 Minimum level
Class 2 Intermediate level
Class 3 Highest level of breathability

Garments with removable sleeves only offer full protection when the sleeves are attached to the body of the garment. Recommended maximum continuous wearing time for a complete suit consisting of jacket and trousers without a thermal lining.



ISO 13688:2013 Protective Clothing (See label)
General Requirements This European Standard specifies general requirements for ergonomics, ageing, sizing, marking of protective clothing and for information supplied by the manufacturer.

- A= Recommended height range of wearer
- B= Recommended chest girth of wearer
- C= Recommended waist girth of wearer
- D= Recommended inside leg measurement of wearer



EN ISO 20471:2013 + A1:2016, High Visibility Warning Clothing signalling the users presence during day and night (see label)

X Classifications (EN ISO 20471:2013 + A1:2016) X Class for the fluorescent and reflective surface - 3 levels

- X Class 1 - Minimum level traffic speeds <30km/h
- X Class 2 - Intermediate level traffic speeds <60km/h
- X Class 3 - Highest level traffic speeds >60km/h



RIS-3279-TOM Issue 1 (2016) :
Railway Industry Standard
RIS-3279-TOM Issue 1 has replaced GO/RIT 3279.
Railway Industry Standards (RIS) are mandatory on all members of the Railway Group and apply to all relevant activities.

Limitations of use (EN ISO 20471:2013 + A1:2016, RIS 3279 & ANSI/ISEA 107-2015): Always wear the garment fastened. Keep clean. Check the High Visibility properties of this garment become irreversibly soiled or contaminated, replace with a new one. This garment is suitable for wear during an entire working day and contains no toxic substances that can affect health adversely in any other way. No allergic reactions due to skin contact with this garment are known. Do not attempt to repair damaged garments. All garments should be discarded safely. The clothing should not be altered or fitted with extra labels or logos. The clothing should only be worn in situations for which it is intended.

Limitations of use (RIS 3279): Class 1 trousers claiming RIS 3279 Compliance are not required to be worn with a RIS 3279 upper body garment.

Wash Care Labels : Refer to garment label for corresponding washing details.

- Max temp 30°C, mild process
- Max temp 40°C, mild process
- Max temp 40°C, normal process
- Max temp 60°C, normal process
- Do Not Bleach
- Do not tumble dry
- Tumble dry low
- Tumble dry normal
- Line dry
- Drip line dry
- Do not iron
- Iron max 110°C
- Iron max 150°C
- Do not dry clean
- Professional dry clean
- MAX Maximum
- 50x 50 Washes
- MAX Maximum
- 25x 25 Washes
- MAX Maximum
- 12x 12 Washes
- MAX Maximum
- 5x 5 Washes