



The following terry knitted para-aramid nitrile lined glove series are supplied by **ScilabubLtd**

CE 0362

STOCKCODE DESCRIPTION SIZE

1515900011	TER/ARA/25	9
1515950031	TER/ARA/35	9
1515970021	TER/ARA/45	9



DECLARATION The above products are in conformity with the regulation (EU) 2016/425 and are identical to the PPE which is subject of EU certificate..... issued by:ITS Testing Services UK Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom NB 0362

Gloves are made to EN 420:2003 sizes and meet the performance levels to EN 388: 2016 and EN 407:2004
 Relevant Harmonized Standards shown

Signed for on behalf of ScilabubLtd

Date: 27/08/2019

Name: Mr M Gee Signature: 

Position: Director

STANDARD EN 388:2016

	Level
Abrasion Resistance	4
Cut Resistance	5
Cut Resistance (TDM)	E
Tear Resistance	4
Puncture Resistance	4



EN 407:2004

Burning Behaviour	4
Contact Heat	3
Convective Heat	4
Radiant Heat	3
Small Drops of molten Metal	X
Large Quantities of Molten Metal	X



GLOVE DESCRIPTION 100% Para-aramid outer terry knittglove lined with nitrile dipped cotton inner. Gloves offer excellent cut resistance and excellent thermal insulation when handling hot objects.

MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels and CE mark. Labels on the gloves will contain similar information. This information will be provided in the minimum resale quantity.

COMPLEX SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with EN388:2016, EN420:2003+A1:2009 & EN407:2004. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. The EC type examination was carried out by ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK. Their test house number is 0362

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

WARNINGS:

Test results apply to the gloves in the as received condition but do not extend to any leather cuff. Result may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

CARE / MAINTENANCE

Cleaning and disinfection is not intended for these gloves. Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands. Washing is not recommended.

Do not wring. Do not tumble dry. Do not use bleach. Gloves may be rinsed in water and allowed to drip dry in ambient temperatures. Reshape whilst still damp.

Warning: 

PACKING AND STORAGE

Can be used under normal climatic conditions.
 Gloves shall be wrapped in polymeric packaging.

Gloves can be used up to five years after date of supply if stored correctly. Store in original packaging. Gloves should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures (between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the glove. The gloves are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

OBSOLESCENCE

Stored correctly, the gloves' physical properties will not change for up to five years.

GENERAL

The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use.

This glove series satisfies the basic requirements of the PPE Regulation (EU) 2016/425 in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified.

Further information is available at the below address:

Scilabub Limited
 9 Huntingdon Court, Measham, Derbyshire, DE12 7NQ, UK.
 T: +44 (0) 1530 279996 F: +44 (0) 1530 270759
<http://www.scilabub.com> email: sales@scilabub.com