

USER INFORMATION

This product has been made to protect against risks as expressed by the pictograms below. These pictograms show where to find the information relating to them on the glove to determine the performance level covered against the specific hazard. Users must be aware that actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer to determine the glove suitability for the intended use.

CE MARK

This type of glove has been subject to an EC type examination by a notified body (see below) according to European standards. The CE mark printed on the gloves signifies that this product is in compliance with the PPE Regulation (EU) 2016/425.

CERTIFIED BY

CTC Groupe, 4, rue Hermann Frenkel, 69367 Lyon cedex, FRANCE
Tel: +33 (0)4 72 76 10 10 Fax: +33 (0)4 72 76 10 00

MAINTENANCE

Both new and used gloves should be inspected to ensure no damage is present prior to use. No specific cleaning or maintenance is advocated as the performance after laundering is unknown.

SIZE GUIDE

The fit dimensions of this glove falls outside the standard length parameters of EN 420:2003. The glove is designed to minimise entanglement risks at the cuff whilst maintaining a dexterous, tactile fit. The end user should fully assess the suitability of the glove to the task prior to first use.

07 - Small 08 - Medium 09 - Large
10 - Xlarge 11 - 2Xlarge

STORAGE

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

OBSOLESCENCE

This product should not deteriorate if stored as recommended (see above) Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

DISPOSAL

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.

ALLERGIC REACTIONS

These gloves may contain Natural Rubber Latex (NRL) and may cause allergic reactions. In the case of an allergic reaction, please discontinue use immediately and seek medical advice. A list of substances is available on request.

EN 388:2016 - MECHANICAL RISKS

Protection against mechanical hazards is expressed by a pictogram followed by five characters (performance levels), each representing test performance against a specific hazard. Levels are only assured on the palm of the glove. The circular blade cut test results are only indicative whilst the straight cut resistance test is the reference performance result.

EN 388:2016



A B C D E

A - Abrasion Resistance [0-4]
B - Blade / Cut Resistance [0-5]
C - Tear Resistance [0-4]
D - Puncture Resistance [0-4]
E - EN ISO 13997 Cut Resistance [A-F]

